




Stone Resin Surfacing

Permeable Paving Solutions



TECHNICAL GUIDE

Paddock Slab



HAHN Paddock Slab is specifically designed for horses. 100% recycled plastic, it's specially formulated to support and cushion the hoof but is strong enough for trucks.

Paddock Slab is specifically designed and tested for horses. The cell wall is thick enough to support large breeds yet the cell aperture is small enough for foal and pony hooves. Paddock Slab is made of hanit® which is 100% recycled plastic and specially formulated to imitate a good equine surface. It cushions and supports the hoof while being strong enough for trucks. Paddock Slab is ideal for:

- » Arena and school surfaces
- » Lunging rings and turnout areas
- » Mud prevention
- » Horse trailers, car and truck parking

OVERVIEW

Material	100% recycled mixed polyolefins
Nominal size	19¾" x 16" x 1⅝"
Unit weight	4.6 lbs
Coverage	2.15 square feet/grid
Compressive strength	465 psi (empty), 73,090 lbs*
	1,350 psi (filled), 228,300 lbs*
	<small>*max. load/unit</small>
Connection type	T connector and slots
Cell wall thickness	¼"
Color	Black
Surface finish	Sand, gravel or grass
Infiltration rate	196"/hr for gravel
Pallet size	45 x 45 x 88" (52 layers of 6)
Pallet details	312 units, 1,485 lbs
Compliant with	USA: Americans with Disabilities Act Canada: Charter of Rights and Freedoms & The Canadian Human Rights Act

TRIED & TESTED

Many standard ground reinforcement grids are simply not up to equine use, the cell walls are often too thin and break and the cells can be too big for smaller hooves. Many standard grids are also made from hard plastics like HDPE that do not cushion the hoof or protect it from impact.

According to the British Horse Society, a horse and rider exerts a greater load than a typical truck due to the much smaller area of a hoof in contact with the ground compared to a truck tire – 185psi compared to a typical truck tire load of 135psi.

This is why HAHN created **Paddock Slab**. Designed, tried and tested for horses.

» Strength and flexibility

The most common testing for heavy duty loads is HS25. During independent testing, Paddock Slab easily met these standards. Even when unfilled, they can bear almost 465 psi (73,090 lbs) and when filled with sand, gravel, soil or grass, **Paddock Slab** can bear 1,350 psi (228,300 lbs). This is more than enough for large horse trailers, trucks and other equine requirements.

Of course, strength without flexibility can lead to cracks, breakages and ultimately product failure. When tested, **Paddock Slab** cell walls are able to flex by more than 10% without breaking.



INTRODUCING hanit®

Developed exclusively by HAHN, **hanit®** is an exceptionally strong, versatile and durable material made from 100% recycled plastic. More than 2,000 HAHN products are made out of **hanit®**, including paving, profiles, fencing, palisades, decking and outdoor furniture – most with a 20-year warranty.

Unlike wood, concrete or steel, weather isn't a problem for **hanit®**. It's also lighter than concrete and cheaper than steel. **hanit®** will not rot or rust, it won't splinter with age or crack in extreme cold. It's easy to work with, looks good all year round and needs little or no maintenance.

hanit® is completely moisture-repellent and does well in wet or damp conditions. It's produced without preservatives, is non-toxic and non-polluting. Best of all, it reduces the strain on landfill and is 100% recyclable.

PADDOCK SLAB & MUD!

Mud is a big problem for horses. It can cause softening of hooves, abscesses, mud fever, tendon/ligament issues, thrush and lost shoes. Good drainage and protecting the ground from being churned up are the best ways to prevent mud. For mud-prone areas like paddock/turnout entrances, feed/watering areas and sacrifice areas, **Paddock Slab** on a free-draining base will solve the problem.

Ideal for:

- » Riding arenas and schools
- » Paddocks and pastures
- » Lunging rings
- » Feeding and watering areas
- » General stable areas
- » Mud control
- » Barn parking and access for horse trailers
- » Pasture access areas

Permeable design

Offers excellent water permeation through the surface preventing mud.

Low maintenance

Quick and easy to install. Comes with a 20-year warranty.

Load capacity

Suitable for AASHTO HS25 loading taking loads of up to 1350psi.

Perfect design

Ideal for horses – smaller cells for hoof support with non-slip ammonia-resistant surface.

Ground erosion


Prevents erosion of earth, ideal at gates and feeding points.

Environmentally friendly

Specially formulated **hanit®** (100% recycled plastic).

Stable

Connection fit improves stability with generous expansion capability.



100% recycled
100% recyclable

TYPICAL INSTALLATION EXAMPLES

Paddock Slab can be used: as a stabilizing layer with a sand tread surface in arenas, pens and walkers; with a gravel fill for general access areas and horse trailer parking; with a grass fill as a mud-prevention measure in paddocks. Whatever purpose **Paddock Slab** serves, good drainage is essential to prevent excessive water mixing with the infill.

Installation without a base

If installed on a stable base, **Paddock Slab** can be used directly over levelled mud due to its strength and wide base. Deformation of the stabilized area should be expected as hooves create extensive point loads.

Preparation of the area

Before installation, remove topsoil and level the base.

Infilling the area

You will need approx. 8ft³ of gravel or topsoil per 100 ft².

Expansion

Paddock Slab has integral T connectors that can absorb up to 1/16" of movement/expansion, eliminating the need for expansion joints. Although separate expansion gaps are not necessary, a 1" gap (filled with gravel or topsoil) should be left between Paddock Slab and curbs or hard edging.




Arenas, schools, exercise areas, round pens & walkers



For a firm yet giving surface, install **Paddock Slab** as a supporting layer onto an area with adequate drainage. Then overlay the slabs with a 3–4" tread layer of sand, rubber, fleece or a purpose-designed riding surface.

» Typical construction

- 1 3-4" tread layer (sand, rubber, fleece etc.)
- 2 1 1/2" **Paddock Slab** filled with angular sand
- 3 1 1/4" compacted sharp sand or grit
- 4 Non-woven 3 oz needle-punched geotextile
- 5 4-12" free-draining sub-base




Paddocks, exercise areas, sacrifice areas, feeding spots, tethering/ mounting areas & paddock gates



For an all-weather grass surface with excellent mud control, install **Paddock Slab** on a free-draining sub-base, backfill the area with topsoil and then seed or turf for use instead of a sacrifice area. For soil-protection and mud-prevention in areas like paddock entrances, extend the **Paddock Slab** area by approximately 16 ft into the paddock – maintenance and mowing are unaffected.

» **Typical construction**

- ❶ Grass finish (seeded or turfed)
- ❷ 1 1/2" **Paddock Slab** filled with topsoil/sand fill
- ❸ 1 1/4" compacted sharp sand or grit
- ❹ Non-woven 3oz needle-punched geotextile
- ❺ 4–12" free-draining sub-base




Access and trails, general stable areas, car parking & horse trailers



For a gravel finish that's suitable for horses, install **Paddock Slab** on a free-draining base. Fill the cells with a well-graded angular gravel (3/16–5/8") and compact. A fine-grit top-dressing will maintain drainage levels and provide good hoof support. **Paddock Slab** is suitable for all horse trailers, including trucks.

» **Typical construction**

- ❶ Angular gravel finish (3/16–5/8")
- ❷ 1 1/2" **Paddock Slab** filled with 3/16–5/8" gravel
- ❸ 1 1/4" compacted sharp sand or grit
- ❹ Non-woven 3 oz needle-punched geotextile
- ❺ 4–12" free-draining sub-base



INSTALLATION

Whether using **Paddock Slab** for an Olympic arena, a local stable or private yard, good drainage is essential. If the area does not have good drainage, supplementary drainage should be installed. If the subgrade is good, the topsoil can be removed and **Paddock Slab** laid directly onto the graded surface – an ideal method for heavy traffic areas like paddock entrances.

Most areas will need a base-layer that supports the surface and lets water drain through to the subgrade. The depth of this base-layer depends on the strength of the subgrade. Subgrade strength is measured by the CBR (Californian Bearing Ratio) and the adjacent table shows CBRs of typical soils.

Soil classification	Relative permeability	Typical CBR	Free-draining
Well graded gravels	Pervious	30 to 80	Yes
Poorly graded gravels	Pervious	20 to 60	Yes
Well graded sand	Pervious	10 to 40	Yes
Poorly graded sand	Semi pervious	10 to 40	Yes
Sandy clay	Impervious	5 to 20	No
Heavy clay	Impervious	3 to 6	No

SUB-BASE DESIGN

When the subgrade CBR is known and the permeability assessed, the depth of free-draining angular stone base can be calculated (note: standard base materials with a high degree of fines are not suitable for free-draining areas). Using a suitable thin plastic geogrid between the subgrade and the granular base can reduce the depth of base as shown below.

Typical use	CBR (%) of subgrade	Angular stone base depth inc. geogrid	Use of geogrid
<ul style="list-style-type: none"> • Small stable areas • Gates • Feeding areas • Around waterers 	Not normally measured	4"	n/a
<ul style="list-style-type: none"> • Indoor and outdoor arenas • Warm-up • Round pens • Paddocks • Yards • Stables 	>6	4"	n/a
	4-6	6"	30/30
	2-4	9"	30/30
	1-2	10"	30/30
<ul style="list-style-type: none"> • Car parking • Loading areas • Horse trailer areas 	>6	6"	n/a
	4-6	7"	30/30
	2-4	11"	30/30
	1-2	19"	30/30

Note: A geogrid is a thin plastic grid used to reinforce soils – if no geogrid is utilized the angular base thicknesses indicated above should be increased by 50%.

OTHER GROUNDWORK & SURFACING PRODUCTS

Hanpave



Heavy Duty Ground Grid



Eco Slab



Decking

